



MS-130

Order No.: 10.1400

Price upon request

PRODUCTINFOS

Hi-fi midrange speaker, 40 W, 8 Ω

- Inverse surround
- Coated cone
- Low moving mass for optimum transient response
- For combinations of a high level stability

TECHNICAL SPECIFICATIONS

MS-130

Impedance (Z)	8 Ω
Frequency range	fx-8,000 Hz
Resonant frequency (fs)	120 Hz
Rec. crossov. frequ. (fmax.) (12 dB/oct.)	300/6,000Hz
Power rating	40 W
Peak music power output	80 W

MS-130

Sensitivity	94 dB/W/m
Suspension compl. (Cms)	0.44 mm/N
Moving mass (Mms)	4 g
Mech. Q factor (Qms)	5.23
Electr. Q factor (Qes)	1.06
Total Q factor (Qts)	0.88
Equivalent volume (Vas)	3 l
DC resistance (Re)	6.1 Ω
Force factor (BxL)	4.2 Tm
Voice coil induct. (Le)	0.25 mH
Voice coil diameter	\varnothing 25.5 mm
Voice coil former	Kapton
Linear excursion (X_{MAX})	\pm 0.7 mm
Eff. cone area (Sd)	70 cm ²
Magnet weight	500 g
Magnet diameter	\varnothing 100 mm
Mounting cutout	\varnothing 120mm
Mounting depth	67 mm
Dimensions	135 x 135 x 70 mm
Width	135 mm
Height	135 mm
Depth	70 mm
Admiss. ambient temp.	0-40 °C
Weight	1.3 kg
Sales unit	1
Type of speaker	5.25"