



# 54/7401 54H/74H01

## QUAD 2-INPUT NAND GATE (With Open-Collector Output)


### CONNECTION DIAGRAMS PINOUT A



### PINOUT B



### PINOUT C



**ORDERING CODE:** See Section 9

PKGS	PIN OUT	COMMERCIAL GRADE	MILITARY GRADE	PKG TYPE
		$V_{CC} = +5.0\text{ V} \pm 5\%$ , $T_A = 0^\circ\text{C to } +70^\circ\text{C}$	$V_{CC} = +5.0\text{ V} \pm 10\%$ , $T_A = -55^\circ\text{C to } +125^\circ\text{C}$	
Plastic	A	7401PC		9A
DIP (P)	B	74H01PC		
Ceramic	A	7401DC	5401DM	6A
DIP (D)	B	74H01DC	54H01DM	
Flatpak (F)	C	7401FC, 74H01FC	5401FM, 54H01FM	3I

**INPUT LOADING/FAN-OUT:** See Section 3 for U.L. definitions

PINS	54/74 (U.L.) HIGH/LOW	54/74H (U.L.) HIGH/LOW
Inputs	1.0/1.0	1.25/1.25
Outputs	OC**/10	OC**/12.5

**DC AND AC CHARACTERISTICS:** See Section 3\*

SYMBOL	PARAMETER	54/74		54/74H		UNITS	CONDITIONS	
		Min	Max	Min	Max		$V_{IN} = \text{Gnd}$	$V_{CC} = \text{Max}$
$I_{CCH}$	Power Supply	8.0		10		mA		
$I_{CCL}$	Current	22		40			$V_{IN} = \text{Open}$	
$t_{PLH}$ $t_{PHL}$	Propagation Delay	45 15		15 12		ns	Figs. 3-2, 3-4	

\*DC limits apply over operating temperature range; AC limits apply at  $T_A = +25^\circ\text{C}$  and  $V_{CC} = +5.0\text{ V}$ .

\*\*OC — Open Collector