


**54/7430**  
**54H/74H30**  
**54S/74S30**  
**54LS/74LS30**  
 8-INPUT NAND GATE


**CONNECTION DIAGRAMS**  
**PINOUT A**



**ORDERING CODE:** See Section 9

PKGS	PIN OUT	COMMERCIAL GRADE	MILITARY GRADE	PKG TYPE
		$V_{CC} = +5.0\text{ V} \pm 5\%$ , $T_A = 0^\circ\text{C to } +70^\circ\text{C}$	$V_{CC} = +5.0\text{ V} \pm 10\%$ , $T_A = -55^\circ\text{C to } +125^\circ\text{C}$	
Plastic DIP (P)	A	7430PC, 74H30PC 74S30PC, 74LS30PC		9A
Ceramic DIP (D)	A	7430DC, 74H30DC 74S30DC, 74LS30DC	5430DM, 54H30DM 54S30DM, 54LS30DM	6A
Flatpak (F)	A	74S30FC, 74LS30FC	54S30FM, 54LS30FM	3I
	B	7430FC, 74H30FC	5430FM, 54H30FM	

**PINOUT B**



**INPUT LOADING/FAN-OUT:** See Section 3 for U.L. definitions

PINS	54/74 (U.L.) HIGH/LOW	54/74H (U.L.) HIGH/LOW	54/74S (U.L.) HIGH/LOW	54/74LS (U.L.) HIGH/LOW
Inputs	1.0/1.0	1.25/1.25	1.25/1.25	0.5/0.25
Outputs	20/10	12.5/12.5	25/12.5	10/5.0 (2.5)

**DC AND AC CHARACTERISTICS:** See Section 3\*

SYMBOL	PARAMETER	54/74		54/74H		54/74S		54/74LS		UNITS	CONDITIONS	
		Min	Max	Min	Max	Min	Max	Min	Max		$V_{IN} = \text{Gnd}$ $V_{CC} = \text{Max}$	Figs. 3-1, 3-4
$I_{CCH}$	Power Supply	2.0		4.2		5.0		0.5		mA		
$I_{CCL}$	Current	6.0		10		10		1.1				
$t_{PLH}$	Propagation Delay	22		10		2.0 6.0		12		ns		
$t_{PHL}$		15		12		2.0 7.0		20				

\*DC limits apply over operating temperature range; AC limits apply at  $T_A = +25^\circ\text{C}$  and  $V_{CC} = +5.0\text{ V}$ .