


54/7432
54S/74S32
54LS/74LS32
 QUAD 2-INPUT OR GATE

CONNECTION DIAGRAM
PINOUT A



ORDERING CODE: See Section 9

PKGS	PIN OUT	COMMERCIAL GRADE	MILITARY GRADE	PKG TYPE
		$V_{CC} = +5.0\text{ V} \pm 5\%$, $T_A = 0^\circ\text{ C to } +70^\circ\text{ C}$	$V_{CC} = +5.0\text{ V} \pm 10\%$, $T_A = -55^\circ\text{ C to } +125^\circ\text{ C}$	
Plastic DIP (P)	A	7432PC, 74S32PC 74LS32PC		9A
Ceramic DIP (D)	A	7432DC, 74S32DC 74LS32DC	5432DM, 54S32DM 54LS32DM	6A
Flatpak (F)	A	7432FC, 74S32FC 74LS32FC	5432FM, 54S32FM 54LS32FM	3I

INPUT LOADING/FAN-OUT: See Section 3 for U.L. definitions

PINS	54/74 (U.L.) HIGH/LOW	54/74S (U.L.) HIGH/LOW	54/74LS (U.L.) HIGH/LOW
Inputs	1.0/1.0	1.25/1.25	0.5/0.25
Outputs	20/10	25/12.5	10/5.0 (2.5)

DC AND AC CHARACTERISTICS: See Section 3 for U.L. definitions

SYMBOL	PARAMETER	54/74		54/74S		54/74LS		UNITS	CONDITIONS	
		Min	Max	Min	Max	Min	Max		$V_{IN} = \text{Open}$	$V_{CC} = \text{Max}$
I_{CCH}	Power Supply Current	22		32		6.2		mA		
I_{CCL}		38		68		9.8			$V_{IN} = \text{Gnd}$	
t_{PLH} t_{PHL}	Propagation Delay	15 22	2.0 2.0	7.0 7.0		15 15		ns	Figs. 3-1, 3-5	

*DC limits apply over operating temperature range; AC limits apply at $T_A = +25^\circ\text{ C}$ and $V_{CC} = +5.0\text{ V}$.