


54/7404
54H/74H04
54S/74S04
54LS/74LS04
HEX INVERTER


CONNECTION DIAGRAMS
PINOUT A



ORDERING CODE: See Section 9

PKGS	PIN OUT	COMMERCIAL GRADE	MILITARY GRADE	PKG TYPE
		$V_{CC} = +5.0\text{ V} \pm 5\%$, $T_A = 0^\circ\text{C to } +70^\circ\text{C}$	$V_{CC} = +5.0\text{ V} \pm 10\%$, $T_A = -55^\circ\text{C to } +125^\circ\text{C}$	
Plastic DIP (P)	A	7404PC, 74H04PC 74S04PC, 74LS04PC		9A
Ceramic DIP (D)	A	7404DC, 74H04DC 74S04DC, 74LS04DC	5404DM, 54H04DM 54S04DM, 54LS04DM	6A
Flatpak (F)	A	74S04FC, 74LS04FC	54S04FM, 54LS04FM	3I
	B	7404FC, 74H04FC	5404FM, 54H04FM	

PINOUT B



INPUT LOADING/FAN-OUT: See Section 3 for U.L. definitions

PINS	54/74 (U.L.) HIGH/LOW	54/74H (U.L.) HIGH/LOW	54/74S (U.L.) HIGH/LOW	54/74LS (U.L.) HIGH/LOW
Inputs	1.0/1.0	1.25/1.25	1.25/1.25	0.5/0.25
Outputs	20/10	12.5/12.5	25/12.5	10/5.0 (2.5)

DC AND AC CHARACTERISTICS: See Section 3*

SYMBOL	PARAMETER	54/74	54/74H	54/74S	54/74LS	UNITS	CONDITIONS
		Min Max	Min Max	Min Max	Min Max		
I_{CCH}	Power Supply	12	26	24	2.4	mA	$V_{IN} = \text{Gnd}$ $V_{CC} = \text{Max}$
I_{CCL}	Current	33	58	54	6.6		$V_{IN} = \text{Open}$
t_{PLH} t_{PHL}	Propagation Delay	22 15	10 10	2.0 4.5 2.0 5.0	10 10	ns	Fig. 3-1, 3-4
t_{PLH} t_{PHL}	Propagation Delay (54/74S04A only)			1.0 3.5 1.0 4.0		ns	Fig. 3-1, 3-4

*DC limits apply over operating temperature range; AC limits apply at $T_A = +25^\circ\text{C}$ and $V_{CC} = +5.0\text{ V}$.