


**54S/74S133**  
**54LS/74LS133**  
 13-INPUT NAND GATE

**CONNECTION DIAGRAM**  
 PINOUT A

**ORDERING CODE:** See Section 9

PKGS	PIN OUT	COMMERCIAL GRADE	MILITARY GRADE	PKG TYPE
		$V_{CC} = +5.0\text{ V} \pm 5\%$ , $T_A = 0^\circ\text{C to } +70^\circ\text{C}$	$V_{CC} = +5.0\text{ V} \pm 10\%$ , $T_A = -55^\circ\text{C to } +125^\circ\text{C}$	
Plastic DIP (P)	A	74S133PC, 74LS133PC		9B
Ceramic DIP (D)	A	74S133DC, 74LS133DC	54S133DM, 54LS133DM	6B
Flatpak (F)	A	74S133FC, 74LS133FC	54S133FM, 54LS133FM	4L



**INPUT LOADING/FAN-OUT:** See Section 3 for U.L. definitions

PINS	54/74S (U.L.) HIGH/LOW	54/74LS (U.L.) HIGH/LOW
Inputs	1.25/1.25	0.5/0.25
Outputs	25/12.5	10/5.0 (2.5)

**DC AND AC CHARACTERISTICS:** See Section 3\*

SYMBOL	PARAMETER	54/74S		54/74LS		UNITS	CONDITIONS	
		Min	Max	Min	Max		$V_{IN} = \text{Gnd}$	$V_{CC} = \text{Max}$
$I_{CCH}$	Power Supply Current	5.0		0.5		mA		
$I_{CCL}$		10		1.1			$V_{IN} = \text{Open}$	
$t_{PLH}$	Propagation Delay	6.0		15		ns	Figs. 3-1, 3-4	
$t_{PHL}$		7.0		38				

\*DC limits apply over operating temperature range; AC limits apply at  $T_A = +25^\circ\text{C}$  and  $V_{CC} = +5.0\text{ V}$ .