


**54S/74S64****4-2-3-2-INPUT AND-OR-INVERT GATE****ORDERING CODE:** See Section 9

PKGS	PIN OUT	COMMERCIAL GRADE	MILITARY GRADE	PKG TYPE
		$V_{CC} = +5.0\text{ V} \pm 5\%$ , $T_A = 0^\circ\text{ C to } +70^\circ\text{ C}$	$V_{CC} = +5.0\text{ V} \pm 10\%$ , $T_A = -55^\circ\text{ C to } +125^\circ\text{ C}$	
Plastic DIP (P)	A	74S64PC		9A
Ceramic DIP (D)	A	74S64DC	54S64DM	6A
Flatpak (F)	A	74S64FC	54S64FM	3I

**CONNECTION DIAGRAM  
PINOUT A****INPUT LOADING/FAN-OUT:** See Section 3 for U.L. definitions

PINS	54/74S (U.L.) HIGH/LOW
Inputs	1.25/1.25
Outputs	25/12.5

**DC AND AC CHARACTERISTICS:** See Section 3\*

SYMBOL	PARAMETER	54/74S		UNITS	CONDITIONS	
		Min	Max			
$I_{CCH}$	Power Supply Current		12.5	mA	$V_{IN} = \text{Gnd}$	$V_{CC} = \text{Max}$
$I_{CCL}$			16		**	
$t_{PLH}$	Propagation Delay	2.0	5.5	ns	Figs. 3-1, 3-4	
$t_{PHL}$		2.0	5.5			

\*DC limits apply over operating temperature range; AC limits apply at  $T_A = +25^\circ\text{ C}$  and  $V_{CC} = +5.0\text{ V}$ .\*\* $I_{CCL}$  is measured with all inputs of one gate open and remaining inputs grounded.