


S5408-A,F,W • N7408-A,F

DIGITAL 54/74 TTL SERIES


SCHEMATIC (each gate)




NOTE: Component values shown are nominal.

PIN CONFIGURATIONS

W PACKAGE



A PACKAGE



RECOMMENDED OPERATING CONDITIONS

Supply Voltage V_{CC} : S5408 Circuits N7408 Circuits	MIN	NOM	MAX	UNIT
	4.5	5	5.5	V
Normalized Fan-Out from Output, N	4.75	5	5.25	V
Operating Free-Air Temperature Range, T_A : S5408 Circuits N7408 Circuits	-55	25	125	°C
	0	25	70	°C

ELECTRICAL CHARACTERISTICS (over recommended operating free-air temperature range unless otherwise noted)

PARAMETER	TEST CONDITIONS*	MIN TYP** MAX			UNIT
		MIN	TYP**	MAX	
$V_{in(1)}$	Logical 1 input voltage required at both input terminals to ensure logical 1 level at output $V_{CC} = \text{MIN}$	2			V
$V_{in(0)}$	Logical 0 input voltage required at either input terminal to ensure logical 0 level at output $V_{CC} = \text{MIN}$			0.8	V
$V_{out(1)}$	Logical 1 output voltage $V_{CC} = \text{MIN}$, $I_{load} = -800\mu\text{A}$	2.4	3.3		V
$V_{out(0)}$	Logical 0 output voltage $V_{CC} = \text{MIN}$, $I_{sink} = 16\text{mA}$		0.22	0.4	V
$I_{in(0)}$	Logical 0 level input current (each input) $V_{CC} = \text{MAX}$			-1.6	mA
$I_{in(1)}$	Logical 1 level input current (each input) $V_{CC} = \text{MAX}$, $V_{in} = 2.4\text{V}$, $V_{in} = 5.5\text{V}$			40 1	μA mA
I_{OS}	Short circuit output current† $V_{CC} = \text{MAX}$	S5408 N7408	-20 -18	-55 -55	mA

ELECTRICAL CHARACTERISTICS (Cont'd)

PARAMETER		TEST CONDITIONS*		MIN	TYP**	MAX	UNIT
$I_{CC(1)}$	Logical 1 level supply current	$V_{CC} = \text{MAX.}$	$V_{in} = 5V$		10	15	mA
$I_{CC(0)}$	Logical 0 level supply current	$V_{CC} = \text{MAX.}$	$V_{in} = 0$		18	26	mA

SWITCHING CHARACTERISTICS, $V_{CC} = 5V$, $T_A = 25^\circ C$, $N = 10$

PARAMETER		TEST CONDITIONS		MIN	TYP	MAX	UNIT
t_{pd0}	Propagation delay time to logical 0 level	$C_L = 15pF$,	$R_L = 400\Omega$		12	19	ns
t_{pd1}	Propagation delay time to logical 1 level	$C_L = 15pF$,	$R_L = 400\Omega$		17.5	27	ns

* For conditions shown as MIN or MAX, use the appropriate value specified under recommended operating conditions for the applicable device type.

** All typical values are at $V_{CC} = 5V$, $T_A = 25^\circ C$

† Not more than one output should be shorted at a time.