



SCHEMATIC (each gate)



PIN CONFIGURATIONS



RECOMMENDED OPERATING CONDITIONS

	MIN	NOM	MAX	UNIT
Supply Voltage V_{CC} : S54H10 Circuits	4.5	5	5.5	V
N74H10 Circuits	4.75	5	5.25	V
Normalized Fan-Out from each Output, N			10	
Operating Free-Air Temperature Range, T_A : S54H10 Circuits	-55	25	125	$^{\circ}C$
N74H10 Circuits	0	25	70	$^{\circ}C$

ELECTRICAL CHARACTERISTICS (over recommended operating free-air temperature range unless otherwise noted)

PARAMETER	TEST CONDITIONS*	MIN	TYP**	MAX	UNIT
$V_{in(1)}$	Logical 1 input voltage required at all input terminals to ensure logical 0 level at output	$V_{CC} = \text{MIN},$	2		V
$V_{in(0)}$	Logical 0 input voltage required of any input terminal to ensure logical 1 level at output	$V_{CC} = \text{MIN},$		0.8	V
$V_{out(1)}$	Logical 1 output voltage	$V_{CC} = \text{MIN},$ $I_{load} = -500\mu A$	2.4		V
$V_{out(0)}$	Logical 0 output voltage	$V_{CC} = \text{MIN},$ $I_{sink} = 20\text{mA}$		0.4	V
$I_{in(0)}$	Logical 0 level input current (each input)	$V_{CC} = \text{MAX},$ $V_{in} = 0.4\text{V}$		-2	mA
$I_{in(1)}$	Logical 1 level input current (each input)	$V_{CC} = \text{MAX},$ $V_{CC} = \text{MAX},$ $V_{CC} = \text{MAX}$	$V_{in} = 2.4\text{V}$ $V_{in} = 5.5\text{V}$	50 1	μA mA
I_{OS}	Short circuit output current†	$V_{CC} = \text{MAX}$	-40	-100	mA

DIGITAL 54/74 TTL SERIES ■ S54H10, N74H10

ELECTRICAL CHARACTERISTICS (Cont'd)

PARAMETER		TEST CONDITIONS		MIN	TYP	MAX	UNIT
$I_{CC(0)}$	Logical 0 level supply current	$V_{CC} = \text{MAX}$,	$V_{in} = 4.5\text{V}$		19.5	30	mA
$I_{CC(1)}$	Logical 1 level supply current	$V_{CC} = \text{MAX}$,	$V_{in} = 0$		7.5	12.6	mA

SWITCHING CHARACTERISTICS, $V_{CC} = 5\text{V}$, $T_A = 25^\circ\text{C}$, $N = 10$

PARAMETER		TEST CONDITIONS		MIN	TYP	MAX	UNIT
t_{pd0}	Propagation delay time to logical 0 level	$C_L = 25\text{pF}$,	$R_L = 280\Omega$		6.3	10	ns
t_{pd1}	Propagation delay time to logical 1 level	$C_L = 25\text{pF}$,	$R_L = 280\Omega$		5.9	10	ns

* For conditions shown as MIN or MAX, use the appropriate value specified under recommended operating conditions for the applicable device type.

** All typical values are at $V_{CC} = 5\text{V}$, $T_A = 25^\circ\text{C}$.

† Not more than one output should be shorted at a time and duration of short circuit test should not exceed 1 second.