

12-Bit Digital-to-Analog Converter with Two-Wire Interface


FEATURES

- 12-Bit Digital-Analog Converter
- 8-Pin SOIC and 8-Pin MSOP Packages
- 2.7–5.5V Single-Supply Operation
- Simple SMBus/I²C Serial Interface
- Low Power - 0.35mA Operation, 0.5µA Shutdown
- Guaranteed Monotonicity

TYPICAL APPLICATIONS

- Programmable Voltage Sources
- Digital-Controlled Amplifiers/Attenuators
- Process Monitoring and Control
- Microprocessor- controlled systems

PIN CONFIGURATION



GENERAL DESCRIPTION


The TC1322 is a serially accessible 12-bit voltage output digital-to-analog converter (DAC). The DAC produces an output voltage that ranges from ground to an externally supplied reference voltage. It operates from a single power supply that can range from 2.7V to 5.5V, making it ideal for a wide range of applications. Built into the part is a power-on reset function that ensures that the device starts at a known condition.

Communication with the TC1322 is accomplished via a simple 2-wire SMBus/I²C compatible serial port with the TC1322 acting as a slave only device. The host can enable the SHDN bit in the CONFIG register to activate the low-power standby mode.


ORDERING INFORMATION

Part No.	Package	Temp. Range
TC1322EOA	8-Pin SOIC (Narrow)	-40°C to +85°C
TC1322EUA	8-Pin MSOP	-40°C to +85°C

FUNCTIONAL BLOCK DIAGRAM



APPLICATIONS DRAWING



12-Bit Digital-to-Analog Converter with Two-Wire Interface

TC1322

ABSOLUTE MAXIMUM RATINGS*

Supply Voltage (V_{DD})	+6V
Voltage On Any Pin	(GND – 0.3V) to (V_{DD} + 0.3V)
Operating Temperature (T_A)	See Below
Storage Temperature (T_{STG})	– 65°C to +150°C
Current On Any Pin	±50 mA
Package Thermal Resistance (θ_{JA})	330°C/W

*Static-sensitive device. Unused devices must be stored in conductive material. Protect devices from static discharge and static fields. Stresses above those listed under Absolute Maximum Ratings may cause permanent damage to the device. These are stress ratings only and functional operation of the device at these or any other conditions above those indicated in the operational sections of the specifications is not implied. Exposure to Absolute Maximum Rating Conditions for extended periods may affect device reliability.

ELECTRICAL CHARACTERISTICS: $V_{DD} = 2.7V$ to $5.5V$, $-40^\circ C \leq T_A \leq +85^\circ C$, unless otherwise noted.

Symbol	Parameter	Test Conditions	Min	Typ	Max	Unit
Power Supply						
V_{DD}	Supply Voltage		2.7	—	5.5	V
I_{DD}	Operating Current	$V_{DD} = 5.5V$, $V_{REF} = 1.2V$ Serial Port Inactive (Note 1)	—	0.35	0.5	mA
$I_{DD-STANDBY}$	Standby Supply Current	$V_{DD} = 3.3V$ Serial Port Inactive (Note 1)	—	0.1	1	μA

STATIC PERFORMANCE—ANALOG SECTION: ($V_{DD} = 2.7V$ to $5.5V$, $V_{REF} = 1.2V$, $-40^\circ C \leq T_A \leq 85^\circ C$, unless otherwise noted.)

Symbol	Parameter	Test Conditions	Min	Typ	Max	Unit
	Resolution		—	—	12	Bits
INL	Integral Non-Linearity at FS, $T_A = 25^\circ C$		—	—	±16	LSB
FSE	Full Scale Error		—	—	±3	%FS
DNL	Differential Non-Linearity, $T_A = 25^\circ C$	All Codes (Note 2)	-1	—	+4	LSB
V_{OS}	Offset Error at V_{OUT}	(Note 2)	—	±0.3	±8	mV
TCV_{OS}	Offset Error Tempco at V_{OUT}		—	10	—	μV/°C
PSRR	Power Supply Rejection Ratio	V_{DD} at DC	—	80	—	dB
V_{REF}	Voltage Reference Range		0	—	$V_{DD} - 1.2$	V
I_{REF}	Reference Input Leakage Current		—	—	±1.0	μA
V_{SW}	Voltage Swing	$V_{REF} \leq (V_{DD} - 1.2V)$	0	—	V_{REF}	V
R_{OUT}	Output Resistance @ V_{OUT}	R_{OUT} (ohmic)	—	5	—	Ω
I_{OUT}	Output Current (Source or Sink)		—	2	—	mA
I_{SC}	Output Short-Circuit Current $V_{DD} = 5.5V$	Source	—	30	50	mA
		Sink	—	20	50	mA

- NOTES:** 1. SDA and SCL must be connected to V_{DD} or GND.
2. Measured at $V_{OUT} \geq 50mV$ referred to GND to avoid output buffer clipping.

12-Bit Digital-to-Analog Converter with Two-Wire Interface

TC1322

DYNAMIC PERFORMANCE: ($V_{DD} = 2.7V$ to $5.5V$, $-40^{\circ}C \leq T_A \leq 85^{\circ}C$, unless otherwise noted.)

Symbol	Parameter	Test Conditions	Min	Typ	Max	Unit
SR	Voltage Output Slew Rate		—	0.8	—	V/ μ s
t _{SETTLE}	Output Voltage Full Scale Settling Time		—	10	—	μ sec
t _{WU}	Wake-up Time		—	20	—	μ s
	Digital Feedthrough and Crosstalk	SDA = V_{DD} , SCL = 100kHz	—	5	—	nV-s

SERIAL PORT INTERFACE: ($V_{DD} = 2.7V$ to $5.5V$, $-40^{\circ}C \leq T_A \leq 85^{\circ}C$, unless otherwise noted.)

Symbol	Parameter	Test Conditions	Min	Typ	Max	Unit
V _{IH}	Logic Input High		2.4	—	V_{DD}	V
V _{IL}	Logic Input Low		—	—	0.6	V
V _{OL}	SDA Output Low	I _{OL} = 3 mA (Sinking Current)	—	—	0.4	V
		I _{OL} = 6 mA	—	—	0.6	V
C _{IN}	Input Capacitance SDA, SCL		—	5	—	pF
I _{LEAK}	I/O Leakage		—	—	± 1	μ A

SERIAL PORT AC TIMING: $V_{DD} = 2.7V$ to $5.5V$, $-40^{\circ}C \leq (T_A = T_J) \leq 85^{\circ}C$; $C_L = 80pF$, unless otherwise noted.)

Symbol	Parameter	Test Conditions	Min	Typ	Max	Unit
f _{SMB}	SMBus Clock Frequency		10	—	100	kHz
t _{IDLE}	Bus Free Time Prior to New Transition		4.7	—	—	μ sec
t _{H(START)}	Start Condition Hold Time		4.0	—	—	μ sec
t _{SU(START)}	Start Condition Setup Time	90% SCL to 10% SDA (for repeated Start Condition)	4.7	—	—	μ sec
t _{SU(STOP)}	Stop Condition Setup Time		4.0	—	—	μ sec
t _{H-DATA}	Data In Hold Time		100	—	—	nsec
t _{SU-DATA}	Data In Setup Time		100	—	—	nsec
t _{LOW}	Low Clock Period	10% to 10%	4.7	—	—	μ sec
t _{HIGH}	High Clock Period	90% to 90%	4	—	—	μ sec
t _F	SMBus Fall Time	90% to 10%	—	—	300	nsec
t _R	SMBus Rise Time	10% to 90%	—	—	1000	nsec
t _{POR}	Power-On Reset Delay	$V_{DD} \geq V_{POR}$ (Rising Edge)	—	500	—	μ sec


PIN DESCRIPTION

Pin No.	Symbol	Type	Description
1	V _{REF}	Input	Voltage Reference Input
2	SDA	Bi-Directional	SMBUS Serial Data
3	SCL	Input	SMBUS Serial Clock
4	GND	Input	System Ground
5	VOUT	Output	Buffered DAC Output
6	NC	None	Not Connected
7	DAC_OUT	Output	Unbuffered DAC Output
8	V _{DD}	Power	Positive Power Supply Input


TC1322

TIMING DIAGRAMS

SMBUS Write Timing Diagram



SMBUS READ Timing Diagram



PIN DESCRIPTION

V_{REF}

Input. Voltage Reference Input can range from 0V to 1.2V below V_{DD} .

SDA

Bi-directional. Serial data is transferred on the SMBus in both directions using this pin. See System Management Bus Specification rev. 1.0 for timing diagrams.

SCL

Input. SMBus serial clock. Clocks data into and out of the TC1322. See System Management Bus Specification rev. 1.0 for timing diagrams.

GND

Input. Ground return for all TC1322 functions.

VOUT

Output. Buffered DAC output voltage. This voltage is a function of the reference voltage and the contents of the DATA register. See Functional Description section.

DAC_OUT

Output. Unbuffered DAC output voltage. This voltage is a function of the reference voltage and the contents of the DATA register. However, since it is unbuffered, care must be taken that the pin is connected only to a high impedance node.

V_{DD}

Input. Positive power supply input. See electrical specifications.

DETAILED DESCRIPTION

The TC1322 is a monolithic 12-bit digital-to-analog converter that is designed to operate from a single supply that can range from 2.7V to 5.5V. The DAC consists of a data register (DATA), a configuration register (CONF), and a current output amplifier. The TC1322 uses an external reference which also determines the maximum output voltage.

The TC1322 uses a current-steering DAC based on an array of matched current sources which goes into the precision resistor that converts the contents of the Data Register and V_{REF} into an output voltage, V_{OUT} given by:

$$V_{OUT} = V_{REF} (DATA / 4096)$$

Reference Input

The reference pin, V_{REF} , is a buffered high impedance input and because of this the load regulation of the reference source need only to be able to tolerate leakage levels of current (less than $1\mu A$). V_{REF} accepts a voltage range from 0 to ($V_{DD} - 1.2V$). Input capacitance is typically around 10 pF.

Output Amplifier

The TC1322 DAC output is buffered with an internal unity-gain rail-to-rail input/output amplifier with a typical slew rate of $0.8V/\mu sec$. Maximum full-scale transition settling time is $10\mu sec$ to within $\pm 1/2$ LSB when loaded with $1k\Omega$ in parallel with 100pF.

Standby Mode

The TC1322 allows the host to put it into a low power ($I_{DD} = 0.5\mu A$, typical) Standby mode. In this mode, the D/A conversion is halted. The SMBus port operates normally. Standby mode is enabled by setting the SHDN bit in the CONFIG register. The table below summarizes this operation.

Standby Mode Operation

SHDN Bit	Operating Mode
0	Normal
1	Standby

SMBus Slave Address

The TC1322 is internally programmed to have a default SMBus address value of 1001 000b. Seven other addresses are available by custom order (contact factory).

SERIAL PORT OPERATION

The Serial Clock input (SCL) and bi-directional data port (SDA) form a 2-wire bi-directional serial port for programming and interrogating the TC1322. The following conventions are used in this bus architecture:

12-Bit Digital-to-Analog Converter with Two-Wire Interface

TC1322

Write 1 Byte Format

S	ADDRESS	WR	ACK	COMMAND	ACK	DATA	ACK	P
	7 Bits			8 Bits		8 Bits		

Slave Address

Command Byte: selects which register you are writing to.

Data Byte: data goes into the register set by the command byte.

Write 2 Byte Format

S	ADDRESS	WR	ACK	COMMAND	ACK	DATA	ACK	DATA	ACK	P
	7 Bits			8 Bits		8 Bits		8 Bits		

Slave Address

Command Byte: selects which register you are writing to.

Data Byte: data goes into the register set by the command byte.

Read 1 Byte Format

S	ADDRESS	WR	ACK	COMMAND	ACK	S	ADDRESS	RD	ACK	DATA	NACK	P
	7 Bits			8 Bits			7 Bits			8 Bits		

Slave Address

Command Byte: selects which register you are reading from.

Slave Address: repeated due to change in data-flow direction.

Data Byte: reads from the register set by the command byte.

Read 2 Byte Format

S	ADDRESS	WR	ACK	COMMAND	ACK	S	ADDRESS	RD	ACK	DATA	ACK	DATA	NACK	P
	7 Bits			8 Bits			7 Bits			8 Bits		8 Bits		

Slave Address

Command Byte: selects which register you are reading from.

Slave Address: repeated due to change in data-flow direction.

Data Byte: reads from the register set by the command byte.

Receive 1 Byte Format

S	ADDRESS	RD	ACK	DATA	NACK	P
	7 Bits			8 Bits		

S = Start Condition

P = Stop Condition

Shaded = Slave Transmission

Data Byte: reads data from the register commanded by the last Read Byte or Write Byte transmission.

Receive 1 Byte Format

S	ADDRESS	RD	ACK	DATA	ACK	DATA	NACK	P
	7 Bits			8 Bits		8 Bits		

S = Start Condition

P = Stop Condition

Shaded = Slave Transmission

Data Byte: reads data from the register commanded by the last Read Byte or Write Byte transmission.

Figure 1. SMBus Protocols

TC1322 Serial Bus Conventions

TERM	EXPLANATION
Transmitter	The device sending data to the bus.
Receiver	The device receiving data from the bus.
Master	The device which controls the bus: initiating transfers (START), generating the clock, and terminating transfers. (STOP)
Slave	The device addressed by the master.
Start	A unique condition signaling the beginning of a transfer indicated by SDA falling (High –Low) while SCL is high.
Stop	A unique condition signaling the end of a transfer indicated by SDA rising (Low –High) while SCL is high.
ACK	A Receiver acknowledges the receipt of each byte with this unique condition. The Receiver drives SDA low during SCL high of the ACK clock-pulse. The Master provides the clock pulse for the ACK cycle.
Busy	Communication is not possible because the bus is in use.
NOT Busy	When the bus is idle, both SDA and SCL will remain high.
Data Valid	The state of SDA must remain stable during the High period of SCL in order for a data bit to be considered valid. SDA only changes state while SCL is low during normal data transfers. (See Start and Stop conditions.)

All transfers take place under control of a host, usually a CPU or microcontroller, acting as the Master, which provides the clock signal for all transfers. The TC1322 *always* operates as a Slave. The serial protocol is illustrated in Figure 1. All data transfers have two phases; all bytes are transferred MSB first. Accesses are initiated by a start condition (START), followed by a device address byte and one or more data bytes. The device address byte includes a Read/Write selection bit. Each access must be terminated by a Stop Condition (STOP). A convention called (ACK) confirms receipt of each byte. Note that SDA can change only during periods when SCL is LOW (SDA changes while SCL is HIGH are reserved for Start and Stop Conditions).

Start Condition (START)

The TC1322 continuously monitors the SDA and SCL lines for a start condition (a HIGH to LOW transition of SDA while SCL is HIGH), and will not respond until this condition is met.

Address Byte

Immediately following the Start Condition, the host must transmit the address byte to the TC1322. The 7-bit SMBus address for the TC1322 is 1001000. The 7-bit address transmitted in the serial bit stream must match for the TC1322 to respond with an Acknowledge (indicating the TC1322 is on the bus and ready to accept data). The eighth bit in the Address Byte is a Read-Write Bit. This bit is a 1 for a read operation or 0 for a write operation. During the first phase of any transfer this bit will be set = 0 to indicate that the command byte is being written.

Acknowledge (ACK)

Acknowledge (ACK) provides a positive handshake between the host and the TC1322. The host releases SDA after transmitting eight bits, then generates a ninth clock cycle to allow the TC1322 to pull the SDA line LOW to acknowledge that it successfully received the previous eight bits of data or address.

Data Byte

After a successful ACK of the address byte, the host must transmit the data byte to be written or clock out the data to be read. (See the appropriate timing diagrams.) ACK will be generated after a successful write of a data byte into the TC1322.

Stop Condition (STOP)

Communications must be terminated by a stop condition (a LOW to HIGH transition of SDA while SCL is HIGH). The Stop Condition must be communicated by the transmitter to the TC1322. NOTE: Refer to Timing Diagrams for serial bus timing.

12-Bit Digital-to-Analog Converter with Two-Wire Interface

TC1322

REGISTER SET AND PROGRAMMER'S MODEL

TC1322 Command Set (SMBus READ_BYTE and WRITE_BYTE)

COMMAND BYTE DESCRIPTION

COMMAND	CODE	FUNCTION
RWD	00h	Read/Write Data (DATA)
RWCR	01h	Read/Write Configuration (CONFIG)

Configuration Register (CONFIG), 8-BITS, READ/WRITE

CONFIGURATION REGISTER (CONFIG)

D[7]	D[6]	D[5]	D[4]	D[3]	D[2]	D[1]	D[0]
RESERVED							SHDN

BIT	POR	FUNCTION	TYPE	OPERATION
D[0]	0	STANDBY switch	ReadWrite	1 = standby, 0 = normal
D[7]-D[1]	0	Reserved - Always returns zero when read.	N/A	N/A

Data Register (DATA), 12-Bits, READ/WRITE

Data Register (DATA) for 1st BYTE

D[11]	D[10]	D[9]	D[8]	D[7]	D[6]	D[5]	D[4]
MSB	X	X	X	X	X	X	LSB

Data Register (DATA) for 2nd BYTE

D[3]	D[2]	D[1]	D[0]	X	X	X	X
X	X	X	LSB	X	X	X	X

The DAC output voltage is a function of reference voltage and the binary value of the contents of the register DATA. The transfer function is given by the expression:

$$V_{OUT} = V_{REF} \times \left[\frac{DATA}{4096} \right]$$

Register Set Summary

The TC1322's register set is summarized below. All registers are 12-bits wide.


NAME	DESCRIPTION	POR State	READ	WRITE
DATA	Data Register (2 BYTE format)	000000000000b*	✓	✓
CONFIG	CONFIG Register	0000 0000b	✓	✓

12-Bit Digital-to-Analog Converter with Two-Wire Interface

TC1322

TAPING FORM


Component Taping Orientation for 8-Pin MSOP Devices



Carrier Tape, Number of Components Per Reel and Reel Size

Package	Carrier Width (W)	Pitch (P)	Part Per Full Reel	Reel Size
8-Pin MSOP	12 mm	8 mm	2500	13 in

Component Taping Orientation for 8-Pin SOIC (Narrow) Devices



Carrier Tape, Number of Components Per Reel and Reel Size


Package	Carrier Width (W)	Pitch (P)	Part Per Full Reel	Reel Size
8-Pin SOIC (N)	12 mm	8 mm	2500	13 in

12-Bit Digital-to-Analog Converter with Two-Wire Interface


TC1322

PACKAGE DIMENSIONS

8-Pin MSOP



8-Pin SOIC (Narrow)



Dimensions: inches (mm)



WORLDWIDE SALES AND SERVICE

AMERICAS

Corporate Office

2355 West Chandler Blvd.
Chandler, AZ 85224-6199
Tel: 480-792-7200 Fax: 480-792-7277
Technical Support: 480-792-7627
Web Address: <http://www.microchip.com>

Rocky Mountain

2355 West Chandler Blvd.
Chandler, AZ 85224-6199
Tel: 480-792-7966 Fax: 480-792-7456

Atlanta

500 Sugar Mill Road, Suite 200B
Atlanta, GA 30350
Tel: 770-640-0034 Fax: 770-640-0307

Austin

Analog Product Sales
8303 MoPac Expressway North
Suite A-201
Austin, TX 78759
Tel: 512-345-2030 Fax: 512-345-6085

Boston

2 Lan Drive, Suite 120
Westford, MA 01886
Tel: 978-692-3848 Fax: 978-692-3821

Boston

Analog Product Sales
Unit A-8-1 Millbrook Tarry Condominium
97 Lowell Road
Concord, MA 01742
Tel: 978-371-6400 Fax: 978-371-0050

Chicago

333 Pierce Road, Suite 180
Itasca, IL 60143
Tel: 630-285-0071 Fax: 630-285-0075

Dallas

4570 Westgrove Drive, Suite 160
Addison, TX 75001
Tel: 972-818-7423 Fax: 972-818-2924

Dayton

Two Prestige Place, Suite 130
Miamisburg, OH 45342
Tel: 937-291-1654 Fax: 937-291-9175

Detroit

Tri-Atria Office Building
32255 Northwestern Highway, Suite 190
Farmington Hills, MI 48334
Tel: 248-538-2250 Fax: 248-538-2260

Los Angeles

18201 Von Karman, Suite 1090
Irvine, CA 92612
Tel: 949-263-1888 Fax: 949-263-1338

Mountain View

Analog Product Sales
1300 Terra Bella Avenue
Mountain View, CA 94043-1836
Tel: 650-968-9241 Fax: 650-967-1590

New York

150 Motor Parkway, Suite 202
Hauppauge, NY 11788
Tel: 631-273-5305 Fax: 631-273-5335

San Jose

Microchip Technology Inc.
2107 North First Street, Suite 590
San Jose, CA 95131
Tel: 408-436-7950 Fax: 408-436-7955

Toronto

6285 Northam Drive, Suite 108
Mississauga, Ontario L4V 1X5, Canada
Tel: 905-673-0699 Fax: 905-673-6509

ASIA/PACIFIC

China - Beijing

Microchip Technology Beijing Office
Unit 915
New China Hong Kong Manhattan Bldg.
No. 6 Chaoyangmen Beidajie
Beijing, 100027, No. China
Tel: 86-10-85282100 Fax: 86-10-85282104

China - Shanghai

Microchip Technology Shanghai Office
Room 701, Bldg. B
Far East International Plaza
No. 317 Xian Xia Road
Shanghai, 200051
Tel: 86-21-6275-5700 Fax: 86-21-6275-5060

Hong Kong

Microchip Asia Pacific
RM 2101, Tower 2, Metroplaza
223 Hing Fong Road
Kwai Fong, N.T., Hong Kong
Tel: 852-2401-1200 Fax: 852-2401-3431

India

Microchip Technology Inc.
India Liaison Office
Divyasree Chambers
1 Floor, Wing A (A3/A4)
No. 11, OI Shaugnessey Road
Bangalore, 560 025, India
Tel: 91-80-2290061 Fax: 91-80-2290062

Japan

Microchip Technology Intl. Inc.
Benex S-1 6F
3-18-20, Shinyokohama
Kohoku-Ku, Yokohama-shi
Kanagawa, 222-0033, Japan
Tel: 81-45-471-6166 Fax: 81-45-471-6122

Korea

Microchip Technology Korea
168-1, Youngbo Bldg. 3 Floor
Samsung-Dong, Kangnam-Ku
Seoul, Korea
Tel: 82-2-554-7200 Fax: 82-2-558-5934

ASIA/PACIFIC (continued)

Singapore

Microchip Technology Singapore Pte Ltd.
200 Middle Road
#07-02 Prime Centre
Singapore, 188980
Tel: 65-334-8870 Fax: 65-334-8850

Taiwan

Microchip Technology Taiwan
11F-3, No. 207
Tung Hua North Road
Taipei, 105, Taiwan
Tel: 886-2-2717-7175 Fax: 886-2-2545-0139

EUROPE

Australia

Microchip Technology Australia Pty Ltd
Suite 22, 41 Rawson Street
Epping 2121, NSW
Australia
Tel: 61-2-9868-6733 Fax: 61-2-9868-6755

Denmark

Microchip Technology Denmark ApS
Regus Business Centre
Lautrup høj 1-3
Ballerup DK-2750 Denmark
Tel: 45 4420 9895 Fax: 45 4420 9910

France

Arizona Microchip Technology SARL
Parc d'Activite du Moulin de Massy
43 Rue du Saule Trapu
Batiment A - 1er Etage
91300 Massy, France
Tel: 33-1-69-53-63-20 Fax: 33-1-69-30-90-79

Germany

Arizona Microchip Technology GmbH
Gustav-Heinemann Ring 125
D-81739 Munich, Germany
Tel: 49-89-627-144 0 Fax: 49-89-627-144-44

Germany

Analog Product Sales
Lochhamer Strasse 13
D-82152 Martinsried, Germany
Tel: 49-89-895650-0 Fax: 49-89-895650-22

Italy

Arizona Microchip Technology SRL
Centro Direzionale Colleoni
Palazzo Taurus 1 V. Le Colleoni 1
20041 Agrate Brianza
Milan, Italy
Tel: 39-039-65791-1 Fax: 39-039-6899883

United Kingdom

Arizona Microchip Technology Ltd.
505 Eskdale Road
Winnersh Triangle
Wokingham
Berkshire, England RG41 5TU
Tel: 44 118 921 5869 Fax: 44-118 921-5820

All rights reserved. © 2001 Microchip Technology Incorporated. Printed in the USA. 1/01  Printed on recycled paper.

01/09/01

Information contained in this publication regarding device applications and the like is intended through suggestion only and may be superseded by updates. It is your responsibility to ensure that your application meets with your specifications. No representation or warranty is given and no liability is assumed by Microchip Technology Incorporated with respect to the accuracy or use of such information, or infringement of patents or other intellectual property rights arising from such use or otherwise. Use of Microchip's products as critical components in life support systems is not authorized except with express written approval by Microchip. No licenses are conveyed, implicitly or otherwise, except as maybe explicitly expressed herein, under any intellectual property rights. The Microchip logo and name are registered trademarks of Microchip Technology Inc. in the U.S.A. and other countries. All rights reserved. All other trademarks mentioned herein are the property of their respective companies.